



Low shrink temperature and space saving

Very thin wall
Flexible and Flame Retardant
U/L and CSA

IP33TW is a very thin wall heat shrinkable polyolefin tubing with a highly flexible, radiation cross-linked tubing used for insulating, jacketing and identification where saving space is important.

Made from flame-retardant polyolefin, it has excellent electrical, chemical and physical properties representing a good all purpose heat shrinkable tubing.

Low shrink temperature reduces install time. Application of heat above 90°C will shrink this tubing quickly to 50% of it's supplied diameter or snug down on the object it is to cover.

Resists a wide range of chemicals and oils as well as sunlight, moisture and fungus.

Specifications:
U/L Subject 224 VW-1 CSA
Longitudinal Shrinkage: less than 5%
Storage: very stable; can be stored over extended intervals without change.
Temperature Rating: continuous operation from -30°C to +125°C.
Electrical: 500 volts per mil.
Standard Colors: black (others special order, available upon request)

Order Size	Expanded Diameter	Recovered	
		Diameter	Wall
3/64"	.046"	.023"	.012"
1/16"	.063"	.031"	.012"
3/32"	.093"	.046"	.012"
1/8"	.125"	.062"	.013"
3/16"	.187"	.093"	.013"
1/4"	.250"	.125"	.014"
3/8"	.375"	.187"	.014"
1/2"	.500"	.250"	.014"
3/4"	.750"	.375"	.017"
1"	1.000"	.500"	.020"