



Works great as a strain relief

- Very flexible polyolefin
- Low shrink temperature
- Highly flame retardant

Very Flexible Heat Shrinkable Polyolefin Tubing is the most flexible tubing we offer. Its high degree of flexibility along with low shrink temperature and high flame retardancy, allow a wide range of applications with a single tubing.

Rated at 135°C this tubing has been engineered to offer a low shrink temperature of 100°C. This allows the tubing to shrink rapidly, thereby minimizing heat exposure and possible damage to sensitive sub-strate materials or components.

This tubing is ideal for aircraft / aerospace assemblies where flexible wire bundling and fire-resistant covering of components is needed.

Specifications:
U/L 224
CSA
AMS-3587
Temperature Rating: -55°C to 135°C
Shrink Temperature: 100°C
Shrink Ratio: 2:1
Electrical: 800 V/mil
Tensile Strength: +/- 5%
Standard Color: black

Order Size	Expanded Diameter	Recovered	
		Diameter	Wall
3/64"	.046"	.023"	.016"
1/16"	.063"	.031"	.017"
3/32"	.093"	.046"	.020"
1/8"	.125"	.062"	.020"
3/16"	.187"	.093"	.020"
1/4"	.250"	.125"	.025"
3/8"	.375"	.187"	.025"
1/2"	.500"	.250"	.025"
3/4"	.750"	.375"	.030"
1"	1.000"	.500"	.035"
1-1/2"	1.500"	.750"	.040"
2"	2.000"	1.000"	.045"